

EEI-BM LINE

Press Out Systems



Front view



Front view: machine with open guards

MAIN FEATURES

- Extrusion of low, medium and high viscosity products
- High strength and efficiency of each single component
- Easy use of the machine
- Easy maintenance
- Attention to detail
- Custom construction configurations
- Design, compact and ergonomic structure that respects aesthetics and handy
- High number of machines sold and operating in the world

MODELS

EPI-BM/EEI-BM: Hydraulic extruder with mobile type tank support bench complete with pneumatic motorization or alternatively electric motorization.

EPI-BF/EEI-BF: Hydraulic extruder with fixed type basin support bench complete with pneumatic motorization or alternatively electric motorization.

EPI-C/EEI-C: Hydraulic extruder with support column complete with pneumatic motorization or alternatively electric motorization.

EPI-M: Mobile hydraulic extruder complete with pneumatic motorization.

EPI-F/EEI-F: Hydraulic extruder for drums complete with pneumatic motorization or alternatively electric motorization.

APPLICATIONS

Glues, Mastics, Greases, Inks, Sealants, Adhesives, Cosmetic Products, Silicones, Dental Pastes, Building Products, Putties

VISCOSITY RANGE

From 20.000 cP up to 10.000.000 cP

PRESSURE ON THE PRODUCT

From 4 Bar up to 20 Bar

CAPACITY RANGE

From 10 Litres up to 2500 Litres

EXTRUDERS



Rear view



Mod. EPI-C/EEI-C: hydraulic extruder with support column completed with pneumatic or alternatively electric motorization



OPTIONS

Management of different levels of ATEX regulations
Movable sealing gaskets
Inflatable seals
Vacuum version
Various systems and protective devices for preventing working accidents.

Mod. EPI-F/EEI-F: hydraulic extruder for drums completed with pneumatic motorization or alternatively electric motorization version



Mod. EPI-M: movable hydraulic extruder completed with pneumatic motorization